

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
28 October 2004 (28.10.2004)

PCT

(10) International Publication Number
WO 2004/093104 A1

- (51) International Patent Classification⁷: **H01F 27/28**, 27/32, H05B 6/66
- (21) International Application Number: PCT/JP2004/005327
- (22) International Filing Date: 14 April 2004 (14.04.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003-110391 15 April 2003 (15.04.2003) JP
- (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006 Oaza Kadoma Kadoma-shi Osaka, 5718501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SAKAI, Shinichi. SATOU, Keiichi. YASUI, Kenji. SUENAGA, Haruo. MORIKAWA, Hisashi.
- (74) Agents: OGURI, Shohei et al.; Eikoh Patent Office 13th Floor ARK Mori Building 12-32 Akasaka 1-chome Minato-ku Tokyo, 1076013 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BOOSTER TRANSFORMER FOR DRIVING MAGNETRON AND TRANSFORMER UNIT HAVING THE BOOSTER TRANSFORMER



$$0.8t_2 < t_1 < 1.1d$$

(57) Abstract: A booster transformer 100 for driving a magnetron includes a bobbin 11 on which at least a first winding 13 and a secondary winding 15 are wound and a core 19 inserted through the center of the bobbin 11, wherein a winding area of the secondary winding 15 is divided into two areas while interposing a partition wall 23, and an outer diameter d of a wire material of the secondary winding 15 and a width t1 of each of the divided winding areas are so set as to satisfy the relation $t_1 < 1.1d$.